Steel Commercial Circulating Wall Fan 24 In. Black/Silver

MODEL CCRF-24-W

Facilities Maintenance / Commercial Circulator Fans

PRODUCT OVERVIEW

The two speed, ball bearing, wall mount commercial circulating fan. Meets OSHA standards and is UL C/US listed. These portable blowers do not have a totally enclosed motor. They should be used in a clean and dry commercial application. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades.

KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Pull chain switch for easy use
- SJT type 3 conductor cord
- Motor is permanently lubricated with split capacitor

CORE PRODUCT DATA

ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
43 lbs	12" W x 27" L x 27" H	43 lbs
PACKAGE 1 SIZE	**COLOR / FINISH**	**FREIGHT TYPE**
8" W x 29" D x 35" H	Black / Silver	Parcel

AVAILABILITY Quote Required - Please Contact Sales **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Blade Diameter (in.)	25
Mounting Style	Wall
Amps High	2.3
CFM High	5400
CFM Low	4300
Electric Motor Horsepower	1/4
Conductor Cord Length (in.)	108
Conductor Cord	SJT type 3
Voltage/Phase	115V/1PH
CFM Medium	4900
OSHA	1910.212 (a)(5)

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Gary, TN 37615**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=123